

TEOS Trap



The TEOS Trap, when used as one element of a TEOS Effluent Management Subsystem™, has proven very effective in reducing particulates and increasing uptime. The TEOS Trap collects TEOS byproducts, preventing them from backstreaming into the furnace and contaminating the pump. In test cases, a greater than 20% reduction in particulates has been recorded.

Maintenance is simplified, by cleaning a single component versus many feet of piping. The large trapping capacity leads to longer preventative maintenance cycles. The high trapping efficiency provides better protection to the pump, valves and other downstream instrumentation.


Product Features

- Improve wafer yields - when used as part of a TEOS Effluent Management Subsystem™
- Overall yield improvement of 2-3%
- Greater than 20% particle reduction
- Increases uptime, reduces downtime
- Easy cleaning and maintenance of Trap
- Protect vacuum pump and valves
- Low cost of ownership - pay back in less than one day
- High flow conductance
- Light weight and compact
- Available in several sizes for use with the most common lines



Applications


Low-pressure chemical vapor deposition using TEOS (tetraethylorthosilicate, $\text{Si}(\text{OC}_2\text{H}_5)_4$) is a popular precursor for the deposition of silicon dioxide as an interlayer dielectric film. The use of TEOS does create problems on the downside of the process chamber in the vacuum pump lines. TEOS and its byproducts have a propensity to clog the vacuum pump line with solid and viscous-liquid effluent byproducts. This increases particle levels, impedes gas flow, and can cause catastrophic pump failure.




Installation Example

Specifications and Ordering Information

Specifications	
Capacity	
6"	• 1.5 lbs. (.68 kg)
8"	• 2.5 lbs. (1.14 kg)
Flow Conductance (Viscous Flow Region)	<ul style="list-style-type: none"> • p = pressure in mTorr • c (sccm/mTorr) = 1.4p • slightly higher than 3" tube
Pressure Drop Across Trap	<ul style="list-style-type: none"> • Q=gas flow rate in sccm • p=pressure in mTorr • $\Delta p=Q/c$
Typical Dry Weight	
6" Angle	• 21 lbs. (9.6 kg)
6" Inline	• 13 lbs. (5.9 kg)
8" Angle	• 26 lbs. (11.8 kg)
8" Inline	• 18 lbs. (8.2 kg)
Flange Seals	Part Number
6" Body, Viton	100760516
6" Body, Kalrez	99T0063
8" Body, Viton	100760520
8" Body, Kalrez	100010228
Replacement Elements	Part Number
6" Body, NW50 or NW80	100012369
8" Body, NW80	100010441
8" Body, NW100	100010225



Dimension A	6"		8"	
	NW50	NW80	NW80	NW100
11.4	12.1	12.1	12.1	
(290)	(307)	(307)	(307)	



Dimension A	6"		8"	
	NW50	NW80	NW80	NW100
5.0	5.0	6.3	6.3	
(127)	(127)	(159)	(159)	
Dimension B	NW50	NW80	NW80	NW100
	11.5	11.5	12.0	12.0
	(292)	(292)	(305)	(305)

Dimensional Drawings -

Note: Unless otherwise specified, dimensions are nominal values in inches.

TEOS Trap Ordering Information

Body TSTRP	Body Size (X)	Port Size (-XXX)	Configuration (-X)	Flanging (-X)	Seal Type (-X)
TSTRP	6 6" Body NW50 & NW80 only	050 NW 50	A Angle	K KF	V Viton®
	8 8" Body NW80 & NW100 only	080 NW 80 100 NW100	I Inline	M MF NW80 & 100 only	K Kalrez®