

New Standards in Performance & Flexibility

EtherCAT® Product Selection Guide



AUTOMATION & CONTROL



PAC 100 Programmable Automation Controller

- Modular, scalable, and configurable programmable control solution
- Supports standard IEC 61131-3 environment
- Seamless interface with HMI, supporting OPC UA



AIO Analog Input/Output Module

- Compact and high density solution for a variety of input and output ranges
- Each AIO module supports 8 analog inputs and 4 analog outputs
- Supporting voltage inputs and outputs are configurable: 0-5V, 0-10V, $\pm 5V$, $\pm 10V$, 0-20mA, 4-20mA (ranges)



ETG.5003.2060

MultiTherm™ 2000 Modular Temperature Controller

- Easily configured for single zone or multi-zone temperature control (48+)
- Ideal for dynamic control applications requiring tight temperature stability
- Precision sensor input channels, accepting RTDs, all thermocouple types, voltage and current inputs
- PID or external Model-Based Control down to 10ms



DIO Digital Input/Output Module

- Integrates digital input and output channels with MKS PAC or CM modules
- Each DIO module supports 12 digital inputs and outputs



CM Communication Fieldbus Coupler Module

- Compact, customizable solution for standalone manual control, data logging, or distributed I/O, or ECAT gateway
- Scalable to any number of MKS I/O slices to create a distributed I/O support for up to hundreds of I/O channels



ETG.5003.1

MicroNode™ Combo Programmable Automation Controller

- Each MicroNode module supports 8 DIO
- Each module supports 16-bit, 8 analog inputs, 4 analog outputs, $\pm 10V$

FLOW / GAS DELIVERY



ETG.5003.2020

G-Series Mass Flow Controllers and Meters

- Full Scale flow rates from 5 sccm to 250 slm
- Proven, patented thermal sensor and mechanical design
- Multi-range/multi-gas capability; 1% of set point accuracy



ETG.5003.2020

I-Series Mass Flow Controllers and Meters

- Full Scale flow rates from 5 sccm to 1000 slm
- IP66-rated enclosure (dustproof & waterproof)
- Multi-range/multi-gas capability; 1% of set point accuracy



ETG.5003.2025

G-Series Pressure Controllers

- Pressure control for Full Scale from 500 Torr to 100 psi
- Thermally stable pressure sensor for 1% of set point accuracy
- Digital flow control algorithm for fast response to set point



ETG.5003.2025

P-Series Pressure Controllers

- Pressure control for Full Scale from 10 to 1000 Torr
- Thermally stable pressure sensor for 1% of set point accuracy
- Flow meter option for backside wafer pressure control applications



DELTA™ Flow Ratio Controllers

- Accurate and repeatable flow ratio control for better process optimization
- For use in cascade configurations
- Operates to temperatures up to 60°C ambient

ETG Profile in Definition Stage

PLASMA SOURCES



Paragon[®] Remote Plasma Sources

- For high gas dissociation rates (>98%) of NF₃
- Gas flows up to 8 slm and pressures up to 10 Torr
- Compatible with O₂ and NF₃ mixed gases



R*evolution[®] Remote Plasma Sources

- Integrated, self-contained unit for on-chamber installation
- Quartz plasma applicator, high density for oxygen species
- Up to 6 kW of plasma power

PRESSURE / VACUUM MEASUREMENT



DA02A Temperature-Controlled Baratron[®] Capacitance Manometer

- Sensor operating temperatures of 45°C, 80°C, 100°C
- Full Scale measurement ranges from 0.1 to 1000 Torr (13.3 Pa to 133.3 kPa)
- Inconel[®]-based sensor offers superior corrosion resistance to common process gases



DA03A High Temperature-Controlled Baratron[®] Capacitance Manometer

- Sensor operating temperatures of 150°C and 160°C
- Optional internally-mounted solid state process relays
- Compact design



901P Load Lock Transducer

- Designed specifically for semiconductor load lock applications
- Providing medium vacuum measurement and atmospheric switching
- Fast and accurate pressure measurement for improved cycle time and particle reduction



925 MicroPirani[™] Vacuum Transducer

- MEMS-based technologies, including MicroPirani[™] technology
- Applicable for foreline and general vacuum measurement applications
- Fast and accurate pressure measurement



972B DualMag[™] Cold Cathode Transducer

- Single transducer with wide pressure measurement range from atmosphere to ultra-high vacuum
- MEMS-based MicroPirani technology combined with cold cathode ionization technology
- Small footprint design provides a compact transducer solution, saving tool real estate

VALVES



T2B Exhaust Throttle Valve

- Advanced model-based pressure control algorithm
- High-speed configurations available (<250 msec. open to close)
- Selectable high torque drives with soft-sealing available



MKS INSTRUMENTS, INC.

1.978.645.5500

1.800.227.8766 (in USA)

www.mksinst.com

