

CF Component

Ultra High Vacuum Fittings

Sizes 1 1/3" to 4 5/8"



Manufactured by MKS to industry standards, Series 88 components are a full line of metal-sealed stainless steel CF flanges and fittings that are interchangeable with ultra high vacuum equipment made by other manufacturers.

MKS offers a complete system of interfacing components including valves, which allows rapid assembly without welding, brazing, or soldering. Most sizes and types of fittings are available for immediate shipment from MKS' distribution centers located throughout North America, Asia, and Europe.

Applications

Series 88 CF flanges are suitable for applications requiring a very clean environment, ultra high vacuum conditions, high temperature, or where critical or dangerous materials must be contained or excluded. These include:

- Difficult applications with corrosive, radioactive, toxic or air sensitive materials
- Materials creation and processing such as molecular beam epitaxy
- Analytical instrumentation including Auger electron spectrometers, mass spectrometers, and electron microscopes
- High energy physics installation such as accelerators and fusion devices

Series 88 is a line of CF-style fittings that are the standard for ultra high vacuum applications. They use a flat gasket placed between two knife edges to provide a vacuum tight seal. Mating flanges have identical profiles, i.e., they are sexless, eliminating the need to store two types or worry about compatibility.



Series 88 Components

- CF Flanges
- Adapters
- Elbows, Tees, Crosses and Bellows
- Thin Metal Hose
- Plate and Nut Sets

Description

Made with very high purity stainless steel and meticulous cleaning procedures, Series 88 CF components are suitable for use in the ultra high vacuum applications to below 10^{-13} Torr and in temperatures from -196° to 500°C. The material characteristics of the flanges, seals, screws, and nuts are selected to provide high performance throughout a wide temperature range. Rotatable and nonrotatable flanges in sizes from mini 1-1/3 to 4-5/8 inches (34 to 117 mm) are available with several bore sizes to fit a range of tube diameters.

MKS uses the latest automated equipment to provide the highest quality and consistency. Very high purity type 304 stainless steel is selected to have few inclusions. Combined with MKS' surface treatment and cleaning procedures, this minimizes outgassing, permeability, and leakage. Proper hardness is maintained to prevent the knife edge from deteriorating.

Installation

CF components are assembled by inserting a gasket between the two flange faces, then securing the assembly with bolts. (See Figure 1.) Bolts should be tightened diagonally, versus sequentially around the circumference, for a secure vacuum seal. Assembly is cost effective through reuse of components and inch dimensional stubs, sockets, and tubes. The foolproof design provides leak tight joints consistently.

A variety of sealing hardware is available, such as plate nuts, dodecagon (12 point head) bolts, Viton® seals, and individually wrapped copper and silver-plated copper gaskets protected from corrosion and mechanical damage.




Figure 1 – CF Flange Installation

Plate nuts furnish the fastest, most convenient method to close flanges, reduce required clearance, assemble with one wrench, and are especially good in limited accessibility. Assembly time reduces greatly, because bolts are easier to start and tighten. The clearance needed is half that of regular nuts. They eliminate the need and cost for tapped flanges.

MKS is one of very few CF manufacturers who offer silver plated bolts, including the convenient dodecagon (12 point head) style, which greatly reduce the risk of seizure or breakage.

Copper gaskets make these flanges self-centering and the standard leak grooves simplify troubleshooting and gasket removal. MKS guarantees its CF flanges and fittings to be leak free. OFHC copper gaskets are cleaned, insured to be scratch free, individually sealed, and ready for use. Individual packaging protects flange seal surfaces.

Silver-plated copper gaskets are available for systems that require frequent high-temperature bakeout. This prevents oxides from forming during the bakeout, which could contaminate the system.

The Viton CF gasket offered by MKS has a unique notching in the design, allowing less outgassing than most elastomer seals.

CF flanges remain leak tight even after repeated cycling of the temperature over a wide range. The availability of both tapped and clearance bolt holes gives great flexibility.

Type 304 stainless steel is suited for assembly by tungsten inert gas (TIG) welding; simple fusion welding without filler metal is preferred. Users may braze components to the CF flanges if desired. CF flanges seal properly when the faces of mating flanges contact each other.

The rotatable versions simplify alignment with the bolt holes of other system components and give infinitely rotatable joints. All fittings have at least one rotatable flange for easy alignment. Nonrotatable flanges provide better knife edge protection. The precise tolerances to which MKS fabricates its CF flanges insure an exact fit every time.

Standard size inch tubing provides easy and economical connection to the user's equipment. Full and half nipples, adapters to a variety of other connection elements, tees, elbows, crosses, and flexible metal hoses for vibration isolation and movement give the line added versatility.

With its extensive engineering capabilities, MKS provides custom designed and manufactured shapes and sizes of components. Custom vacuum chambers can be fabricated as well as unique space and time saving fittings and adapters.

Specifications							
Minimum Pressure (with metal seals)	10 ⁻¹³ Torr						
Leak Check	< 10 ⁻⁹ std-cc/s						
Materials	<table> <tr> <td>Components</td><td>• Type 304 Stainless Steel</td></tr> <tr> <td>Gaskets</td><td>• Copper, Silver Plated Copper or Viton</td></tr> <tr> <td>Bolts</td><td>• Type 304 Stainless or Silver Plated Stainless</td></tr> </table>	Components	• Type 304 Stainless Steel	Gaskets	• Copper, Silver Plated Copper or Viton	Bolts	• Type 304 Stainless or Silver Plated Stainless
Components	• Type 304 Stainless Steel						
Gaskets	• Copper, Silver Plated Copper or Viton						
Bolts	• Type 304 Stainless or Silver Plated Stainless						
Metal Gasket Thickness	.08"/(2.03 mm)						

Size	Metal Gasket Dimensions in/(mm)		Maximum Torque for Sealing ft/lbs (Newton-meters)
	Outer Diameter	Inner Diameter	
1 1/3"	0.84/(21)	0.64/(16)	5/(7)
2 1/8"	1.29/(33)	1.01/(26)	16/(22)
2 3/4"	1.90/(48)	1.45/(37)	16/(22)
3 3/8"	2.43/(62)	2.01/(51)	26/(35)
4 1/2"	3.24/(82)	2.51/(64)	26/(35)
4 5/8"	3.60/(91)	3.01/(76)	26/(35)


Note: Metal gaskets are .08" thick.

Table 1 — Gaskets and Torques


CF Flange Dimensions

in/mm

Flange Size	A Nominal Tube Diameter	B Flange Outside Diameter	C Bolt Circle Diameter	D Thickness	E Number of Holes	Tapped Holes Thread	Thru Holes Diameter	F Face to Counter Bore
1 1/3	.75 (19)	1.33 (34)	1.06 (27)	.30 (8)	6	8-32	.172 (4.3)	.18 (4.6)
2 1/8	1.00 (25)	2.12 (54)	1.62 (41)	.50 (13)	4	1/4-28	.265 (6.7)	.17 (4.3)
2 3/4	1.50 (38)	2.75 (70)	2.31 (59)	.50 (13)	6	1/4-28	.265 (6.7)	.21 (5.3)
3 3/8	2.00 (51)	3.38 (86)	2.85 (72)	.69 (18)	8	5/16-24	.332 (8.4)	.22 (5.6)
4 1/2	2.50 (64)	4.50 (114)	3.63 (92)	.69 (18)	8	5/16-24	.332 (8.4)	.38 (9.6)
4 5/8	3.01 (76)	4.61 (118)	4.03 (102)	.75 (19)	10	5/16-24	.332 (8.4)	.38 (9.6)



Rotatable



Non-Rotatable




CF Flanges

in/mm

Flange Size	For Tubing OD	Rotatable / Non-Rotatable	Bolt Holes	Part Number
1 1/3	Blank	Rotatable	Thru	100881014
1 1/3	Blank	Rotatable	Tapped	100881021
1 1/3	Blank	Non-Rotatable	Thru	100881000
1 1/3	Blank	Non-Rotatable	Tapped	100881007
1 1/3	.75 (19)	Rotatable	Thru	100881018
1 1/3	.75 (19)	Rotatable	Tapped	100881025
1 1/3	.75 (19)	Non-Rotatable	Thru	100881004
1 1/3	.75 (19)	Non-Rotatable	Tapped	100881011
2 1/8	Blank	Rotatable	Thru	100882010
2 1/8	Blank	Rotatable	Tapped	100882015
2 1/8	Blank	Non-Rotatable	Thru	100882000
2 1/8	Blank	Non-Rotatable	Tapped	100882005
2 1/8	.25 (6)	Rotatable	Thru	100882011
2 1/8	.25 (6)	Rotatable	Tapped	100882016
2 1/8	.25 (6)	Non-Rotatable	Thru	100882001
2 1/8	.25 (6)	Non-Rotatable	Tapped	100882006
2 1/8	.50 (13)	Rotatable	Thru	100882012
2 1/8	.50 (13)	Rotatable	Tapped	100882017
2 1/8	.50 (13)	Non-Rotatable	Thru	100882002
2 1/8	.50 (13)	Non-Rotatable	Tapped	100882007
2 1/8	.75 (19)	Rotatable	Thru	100882013
2 1/8	.75 (19)	Rotatable	Tapped	100882018
2 1/8	.75 (19)	Non-Rotatable	Thru	100882003
2 1/8	.75 (19)	Non-Rotatable	Tapped	100882008
2 1/8	1.00 (25)	Rotatable	Thru	100882014
2 1/8	1.00 (25)	Rotatable	Tapped	100882019
2 1/8	1.00 (25)	Non-Rotatable	Thru	100882004
2 1/8	1.00 (25)	Non-Rotatable	Tapped	100882009
2 3/4	Blank	Rotatable	Thru	100883014
2 3/4	Blank	Rotatable	Tapped	100883021

CF Flanges				in/mm
Flange Size	For Tubing OD	Rotatable / Non-Rotatable	Bolt Holes	Part Number
2 3/4	Blank	Non-Rotatable	Thru	100883000
2 3/4	Blank	Non-Rotatable	Tapped	100883007
2 3/4	.25 (6)	Rotatable	Thru	100883015
2 3/4	.25 (6)	Rotatable	Tapped	100883022
2 3/4	.25 (6)	Non-Rotatable	Thru	100883001
2 3/4	.25 (6)	Non-Rotatable	Tapped	100883008
2 3/4	.50 (13)	Rotatable	Thru	100883016
2 3/4	.50 (13)	Rotatable	Tapped	100883023
2 3/4	.50 (13)	Non-Rotatable	Thru	100883002
2 3/4	.50 (13)	Non-Rotatable	Tapped	100883009
2 3/4	.75 (19)	Rotatable	Thru	100883017
2 3/4	.75 (19)	Rotatable	Tapped	100883024
2 3/4	.75 (19)	Non-Rotatable	Thru	100883003
2 3/4	.75 (19)	Non-Rotatable	Tapped	100883010
2 3/4	1.00 (25)	Rotatable	Thru	100883018
2 3/4	1.00 (25)	Rotatable	Tapped	100883025
2 3/4	1.00 (25)	Non-Rotatable	Thru	100883004
2 3/4	1.00 (25)	Non-Rotatable	Tapped	100883011
2 3/4	1.25 (32)	Rotatable	Thru	100883019
2 3/4	1.25 (32)	Rotatable	Tapped	100883026
2 3/4	1.25 (32)	Non-Rotatable	Thru	100883005
2 3/4	1.25 (32)	Non-Rotatable	Tapped	100883012
2 3/4	1.50 (38)	Rotatable	Thru	100883020
2 3/4	1.50 (38)	Rotatable	Tapped	100883027
2 3/4	1.50 (38)	Non-Rotatable	Thru	100883006
2 3/4	1.50 (38)	Non-Rotatable	Tapped	100883013
2 3/4	1.75 (45)	Rotatable	Thru	100883065
2 3/4	1.75 (45)	Rotatable	Tapped	100883067
2 3/4	1.75 (45)	Non-Rotatable	Thru	100883064
2 3/4	1.75 (45)	Non-Rotatable	Tapped	100883066
3 3/8	Blank	Rotatable	Thru	100884006
3 3/8	Blank	Rotatable	Tapped	100884009
3 3/8	Blank	Non-Rotatable	Thru	100884000
3 3/8	Blank	Non-Rotatable	Tapped	100884003
3 3/8	1.50 (38)	Rotatable	Thru	100884007
3 3/8	1.50 (38)	Rotatable	Tapped	100884010
3 3/8	1.50 (38)	Non-Rotatable	Thru	100884001
3 3/8	1.50 (38)	Non-Rotatable	Tapped	100884004
3 3/8	2.00 (51)	Rotatable	Thru	100884008
3 3/8	2.00 (51)	Rotatable	Tapped	100884011
3 3/8	2.00 (51)	Non-Rotatable	Thru	100884002
3 3/8	2.00 (51)	Non-Rotatable	Tapped	100884005
4 1/2	Blank	Rotatable	Thru	100885008
4 1/2	Blank	Rotatable	Tapped	100885012
4 1/2	Blank	Non-Rotatable	Thru	100885000
4 1/2	Blank	Non-Rotatable	Tapped	100885004
4 1/2	1.50 (38)	Rotatable	Thru	100885009
4 1/2	1.50 (38)	Rotatable	Tapped	100885013
4 1/2	1.50 (38)	Non-Rotatable	Thru	100885001
4 1/2	1.50 (38)	Non-Rotatable	Tapped	100885005
4 1/2	2.00 (51)	Rotatable	Thru	100885010
4 1/2	2.00 (51)	Rotatable	Tapped	100885014
4 1/2	2.00 (51)	Non-Rotatable	Thru	100885002
4 1/2	2.00 (51)	Non-Rotatable	Tapped	100885006
4 1/2	2.50 (64)	Rotatable	Thru	100885011
4 1/2	2.50 (64)	Rotatable	Tapped	100885015
4 1/2	2.50 (64)	Non-Rotatable	Thru	100885003
4 1/2	2.50 (64)	Non-Rotatable	Tapped	100885007
4 5/8	Blank	Rotatable	Thru	100885504
4 5/8	Blank	Rotatable	Tapped	100885506
4 5/8	Blank	Non-Rotatable	Thru	100885500
4 5/8	Blank	Non-Rotatable	Tapped	100885502
4 5/8	3.00 (76)	Rotatable	Thru	100885505
4 5/8	3.00 (76)	Rotatable	Tapped	100885507
4 5/8	3.00 (76)	Non-Rotatable	Thru	100885501
4 5/8	3.00 (76)	Non-Rotatable	Tapped	100885503

CF Half Nipple



- Butt weld
- For use with orbital welders
- Thru holes

Flange Size

For Tubing Size
(OD)


A

B

in/mm

Flange Size	For Tubing Size (OD)	A	B	Part Number
1 1/3	.75 (19)	.62 (16)	1.50 (38)	100881046
2 1/8	1.00 (25)	.87 (22)	2.05 (52)	100882040
2 3/4	1.50 (38)	1.37 (35)	2.43 (62)	100883049
3 3/8	2.00 (51)	1.87 (47)	3.21 (82)	100884027
4 1/2	2.50 (64)	2.37 (60)	4.13 (105)	100885032
4 5/8	3.00 (76)	2.87 (73)	4.93 (125)	100885531

CF Full Nipple



- Special lengths to order
- Thru holes

* Includes 12 mesh screen, 1/2" in from rotatable port

Flange Size


For Tubing Size
(OD)

A

B


in/mm

Flange Size	For Tubing Size (OD)	A	B	Part Number
1 1/3	.75 (19)	.62 (16)	3.00 (76)	100881047
2 1/8	1.00 (25)	.87 (22)	4.10 (104)	100882041
2 3/4	1.50 (38)	1.37 (35)	4.92 (125)	100883050
2 3/4*	1.50 (38)	1.37 (35)	4.00 (102)	100883069
3 3/8	2.00 (51)	1.87 (47)	6.42 (163)	100884028
4 1/2	2.50 (64)	2.37 (60)	8.26 (210)	100885033
4 5/8	3.00 (76)	2.87 (73)	9.88 (250)	100885532

Adapter, ISO-KF to CF


- Stainless steel type 304


Flange Size (KF)	Flange Size (CF)	A	B	Part Number
NW 16	Mini 1 1/3	2.08 (53)	0.62 (16)	100315601
NW 16	2 3/4	1.78 (45)	0.62 (16)	100315611
NW 25	2 1/8	1.89 (48)	0.87 (22)	100319812
NW 25	2 3/4	1.78 (45)	0.87 (22)	100315603
NW 40	2 3/4	1.78 (45)	1.33 (34)	100315605
NW 50	2 3/4	2.11 (54)	1.37 (35)	100319813
NW 50	4 1/2	1.95 (50)	1.83 (46)	100315606

Adapter, ISO-MF Flange to CF Flange


- Stainless steel type 304
- Special adapters available upon request

Flange Size	A	B	C	Part Number
NW 63 to 4 1/2" CF	4.33 (110)	2.37 (60)	4.50 (114)	100762206


Adapter, CF to VCR® Female



- Thru holes
- VCR-compatible parts may be used

Flange Size	A	B	VCR Size	Part Number
1 1/3 to 4 VCR	1.43 (36)	.19 (5)	1/4	100881049
2 1/8 to 4 VCR	1.50 (38)	.19 (5)	1/4	100882032
2 1/8 to 8 VCR	1.69 (43)	.41 (10)	1/2	100882033
2 1/8 to 12 VCR	2.19 (56)	.62 (16)	3/4	100882036
2 3/4 to 4 VCR	1.50 (38)	.19 (5)	1/4	100883054
2 3/4 to 8 VCR	1.69 (43)	.41 (10)	1/2	100883057
2 3/4 to 12 VCR	2.19 (56)	.62 (16)	3/4	100883058
3 3/8 to 4 VCR	1.80 (46)	.19 (5)	1/4	100884033
3 3/8 to 8 VCR	1.88 (48)	.41 (10)	1/2	100884035
3 3/8 to 12 VCR	2.38 (60)	.62 (16)	3/4	100884037

Adapter, CF to VCR® Male




- Thru holes
- VCR-compatible parts may be used

Flange Size	A	B	VCR Size	Part Number
1 1/3 to 4 VCR	1.43 (36)	.19 (5)	1/4	100881050
2 1/8 to 4 VCR	1.50 (38)	.19 (5)	1/4	100882031
2 1/8 to 8 VCR	1.69 (43)	.41 (10)	1/2	100882034
2 1/8 to 12 VCR	2.19 (56)	.62 (16)	3/4	100882035
2 3/4 to 4 VCR	1.50 (38)	.19 (5)	1/4	100883055
2 3/4 to 8 VCR	1.69 (43)	.41 (10)	1/2	100883056
2 3/4 to 12 VCR	2.19 (56)	.62 (16)	3/4	100883059
3 3/8 to 4 VCR	1.80 (46)	.19 (5)	1/4	100884032
3 3/8 to 8 VCR	1.88 (48)	.41 (10)	1/2	100884034
3 3/8 to 12 VCR	2.38 (60)	.62 (16)	3/4	100884036

CF Elbow 45° Smooth Radius

in/mm



- Flanges same size on both sides

Flange Size

For Tubing Size (OD)


A

Part Number

1 1/3	.75 (19)	.81 (21)	100881052
2 1/8	1.00 (25)	1.35 (34)	100882038
2 3/4	1.50 (38)	1.82 (46)	100883061
3 3/8	2.00 (51)	2.53 (64)	100884039
4 1/2	2.50 (64)	3.37 (86)	100885037
4 5/8	3.00 (76)	4.05 (103)	100885528

CF Elbow 90° Smooth Radius

in/mm



- Flanges same size on both sides

Flange Size

For Tubing Size (OD)


A

Part Number

1 1/3	.75 (19)	1.50 (38)	100881030
2 1/8	1.00 (25)	2.22 (56)	100882039
2 3/4	1.50 (38)	2.46 (63)	100883030
3 3/8	2.00 (51)	3.21 (82)	100884014
4 1/2	2.50 (64)	4.13 (105)	100885018
4 5/8	3.00 (76)	4.86 (123)	100885529

CF Tee

in/mm



- Flanges same size on all sides

Flange Size

For Tubing OD

A


B

Part Number

1 1/3	.75 (19)	1.50 (38)	3.00 (76)	100881028
2 1/8	1.00 (25)	2.06 (52)	4.12 (105)	100882042
2 3/4	1.50 (38)	2.46 (63)	4.92 (125)	100883028
3 3/8	2.00 (51)	3.21 (82)	6.42 (166)	100884012

CF Cross

in/mm



- Flanges same size on all sides

Flange Size

For Tubing OD


A

B

Part Number

1 1/3	.75 (19)	1.50 (38)	3.00 (76)	100881029
2 1/8	1.00 (25)	2.06 (52)	4.12 (105)	100882043
2 3/4	1.50 (38)	2.46 (63)	4.92 (125)	100883029
3 3/8	2.00 (51)	3.21 (82)	6.42 (166)	100884013


Bellows Section



- Type 321 stainless steel
- Flexible coupling for vibrations and alignment
- Thru holes

	Flange Size	Static Bend Radius	A	B	Spring Rate (lb/in)	in/mm	Part Number
	1 1/3	3.0 (76)	4.15 (105)	3.80 (97)	70		100881045
	2 1/8	4.0 (102)	3.41 (86)	3.20 (81)	58		100882028
	2 3/4	5.5 (140)	4.15 (105)	3.20 (81)	61		100883047
	3 3/8	8.0 (203)	4.29 (109)	3.20 (81)	58		100884025

Thin Wall Metal Hose



- Type 321 stainless steel
- Special lengths to order
- Both ends must be supported for the 4 1/2 and 6 inch sizes

	Flange Size	Static Bend Radius	A	B	Wall Thickness	Spring Rate (lb/in)	in/mm	Part Number
	1 1/3	1.63 (41)	11.3 (287)	7.8 (198)	.006 (.152)	27		100881032
	1 1/3	1.63 (41)	21.2 (539)	13.8 (351)	.006 (.152)	12		100881033
	1 1/3	1.63 (41)	40.9 (1039)	25.6 (650)	.006 (.152)	9		100881034
	2 1/8	1.38 (35)	11.3 (287)	7.8 (198)	.006 (.152)	16		100882020
	2 1/8	1.38 (35)	22.1 (561)	14.7 (373)	.006 (.152)	7		100882021
	2 1/8	1.38 (35)	41.8 (1062)	26.5 (673)	.006 (.152)	3		100882022
	2 3/4	2.50 (64)	12.3 (312)	8.7 (221)	.006 (.152)	9		100883032
	2 3/4	2.50 (64)	22.1 (561)	14.1 (358)	.006 (.152)	4		100883033
	2 3/4	2.50 (64)	41.9 (1064)	25.0 (635)	.006 (.152)	2		100883034
	3 3/8	3.25 (83)	13.3 (338)	10.5 (267)	.006 (.152)	13		100884016
	3 3/8	3.25 (83)	23.2 (589)	17.0 (432)	.006 (.152)	6		100884017
	3 3/8	3.25 (83)	42.9 (1090)	29.8 (757)	.006 (.152)	3		100884018
	4 1/2	6.75 (172)	13.8 (351)	9.1 (231)	.006 (.152)	15		100885020
	4 1/2	6.75 (172)	23.7 (602)	16.2 (412)	.006 (.152)	7		100885021
	4 1/2	6.75 (172)	43.4 (1102)	30.3 (770)	.006 (.152)	3		100885022

Flange Protector Caps

Flange Size	Description	Part Number
1 1/3	Flange protector cap, plastic	100003050
2 1/8	Flange protector cap, plastic	100005285
2 3/4	Flange protector cap, plastic	100003049
3 3/8	Flange protector cap, plastic	100003048

CF Hardware			
Flange Size	Description	Quantity	Part Number
1 1/3 1 1/3 1 1/3 1 1/3 2 1/8, 2 3/4 3 3/8, 4 1/2, 4 5/8	Bolt Set, Tapped, 8-32 x 0.56 Bolt Set, Tapped, 8-32 x 0.62 Bolt Set, Tapped, 8-32 x 0.75 Bolt Set, Tapped, 8-32 x 0.50 Bolt Set, Tapped, 1/4-28 x 1.00 Bolt Set, Tapped, 5/16-24 x 1.25	25 25 25 25 25 25	100889029 100889030 100889031 100889032 100889033 100889035
1 1/3 1 1/3 1 1/3 1 1/3 2 1/8, 2 3/4 2 1/8, 2 3/4 3 3/8 4 1/2 4 5/8	Bolt/Nut Set, Thru, 8-32 x 0.75 Bolt/Nut Set, Thru, 8-32 x 0.87 Bolt/Nut Set, Thru, 8-32 x 0.75, Ag Bolt/Nut Set, Thru, 8-32 x 0.87, Ag Bolt/Nut Set, Thru, 1/4-28 x 1.25 Bolt/Nut Set, Thru, 1/4-28 x 1.38 Bolt/Nut Set, Thru, 5/16-24 x 1.75 Bolt/Nut Set, Thru, 5/16-24 x 2.00 Bolt/Nut Set, Thru, 5/16-24 x 2.25	25 25 25 25 25 25 25 25 25	100889047 100889147 100889048 100889148 100889049 100889150 100889051 100889053 100889055
1 1/3 1 1/3 2 1/8, 2 3/4 2 3/4 2 3/4 3 3/8 4 1/2 4 5/8	Bolt/Nut Set, Double-Sided, 8-32 x 1.25 Bolt/Nut Set, Double-Sided, 8-32 x 1.25, Ag Bolt/Nut Set, Double-Sided, 1/4-28 x 1.75 Bolt/Nut Set, Double-Sided, 1/4-28 x 2.00 Bolt/Nut Set, Double-Sided, 1/4-28 x 2.50 Bolt/Nut Set, Double-Sided, 5/16-24 x 2.50 Bolt/Nut Set, Double-Sided, 5/16-24 x 2.75 Bolt/Nut Set, Double-Sided, 5/16-24 x 3.00	25 25 25 25 25 25 25 25	100889123 100889124 100889125 100889126 100889153 100889130 100889127 100889128
1 1/3 2 1/8 2 3/4 3 3/8 4 1/2 4 5/8	Viton Seal, Beveled Edge Viton Seal, Beveled Edge	5 5 5 5 5 5	100889020 100889021 100889022 100889023 100889024 100889025
CF Hardware			
Flange Size	Description	Quantity	Part Number
1 1/3 2 1/8 2 3/4 3 3/8 4 1/2 4 5/8	Silver-Plated Copper Gasket Silver-Plated Copper Gasket Silver-Plated Copper Gasket Silver-Plated Copper Gasket Silver-Plated Copper Gasket Silver-Plated Copper Gasket	1 1 1 1 1 1	100889181 100889182 100889183 100889184 100889185 100889186
1 1/3 2 1/8 2 3/4 3 3/8 4 1/2 4 5/8	Copper Gasket, Etched, Individually Sealed Copper Gasket, Etched, Individually Sealed	10 10 10 10 10 10	100889103 100889104 100889105 100889106 100889107 100889108

Plate Nut Sets





Plate Nut (24 per package)

Flange Size	Thread Size	A	B	C	D	Part Number
1 1/3	8-32	.80"	.30"	.53"	.15"	100889071
2 3/4	1/4-28	1.41"	.50"	1.16"	.18"	100889072
3 3/8	5/16-24	1.75"	.50"	1.09"	.22"	100889073
4 1/2	5/16-24	2.03"	.50"	1.39"	.22"	100889074

Plate Nut and Bolt Sets

Flange Size	Description	Part Number
1 1/3	Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 8-32 x 0.75	100889077
2 3/4	Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 1/4-28 x 1.25	100889079
3 3/8	Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24 x 1.75	100889081
4 1/2	Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24 x 2.00	100889083

Plate Nut and Dodecagon (12 pt) Silver Plated Bolt Sets

Flange Size	Description	Part Number
1 1/3	Dodecagon Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 8-32 x 0.75	100889090
2 3/4	Dodecagon Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 1/4-28 x 1.25	100889092
3 3/8	Dodecagon Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24 x 1.75	100889094
4 1/2	Dodecagon Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24 x 2.00	100889096

Dodecagon (12 pt) Bolts with Nuts and Washers*

Flange Size	Description	Part Number
2 1/8, 2 3/4	Dodecagon Bolt/Nut/Washer Set, Silver Plated, Tapped, 1/4-28 x 1.00	100889042
2 1/8, 2 3/4	Dodecagon Bolt/Nut/Washer Set, Silver Plated, Thru, 1/4-28 x 1.25	100889062
2 1/8, 2 3/4	Dodecagon Bolt/Nut/Washer Set, Silver Plated, Thru, 1/4-28 x 1.38	100889151
3 3/8, 4 1/2, 4 5/8	Dodecagon Bolt/Nut/Washer Set, Silver Plated, Tapped, 5/16-24 x 1.25	100889044
4 1/2	Dodecagon Bolt/Nut/Washer Set, Silver Plated, Thru, 5/16-24 x 2.00	100889066
3 3/8	Dodecagon Bolt/Nut/Washer Set, Silver Plated, Thru, 5/16-24 x 1.75	100889064
4 5/8	Dodecagon Bolt/Nut/Washer Set, Silver Plated, Thru, 5/16-24 x 2.25	100889068

* Note: There are 25 bolts, nuts, and washers per package.

Type	Part Number	Type	Part Number
45° Elbow, 1 1/3"	100881052	Cross, 1 1/3"	100881029
45° Elbow, 2 1/8"	100882038	Cross, 2 1/8"	100882043
45° Elbow, 2 3/4"	100883061	Cross, 2 3/4"	100883029
45° Elbow, 3 3/8"	100884039	Cross, 3 3/8"	100884013
45° Elbow, 4 1/2"	100885037	Dodecagon Bolt/Nut/Washer Set, Tapped, 1/4-28x1.00, 2 1/8", 2 3/4"	100889042
45° Elbow, 4 5/8"	100885528	Dodecagon Bolt/Nut/Washer Set, Tapped, 5/16-24x1.75, 3 3/8", 4 1/2", 4 5/8"	100889044
90° Elbow, 1 1/3"	100881030	Dodecagon Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 8-32x0.75, 1 1/3"	100889090
90° Elbow, 2 1/8"	100882039	Dodecagon Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 1/4-28x1.25, 2 3/4"	100889092
90° Elbow, 2 3/4"	100883030	Dodecagon Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24x1.75, 3 3/8"	100889094
90° Elbow, 3 3/8"	100884014	Dodecagon Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24x2.00, 4 1/2"	100889096
90° Elbow, 4 1/2"	100885018	Dodecagon Bolt/Nut/Washer Set, Thru, 1/4-28x1.25, 2 1/8", 2 3/4"	100889062
90° Elbow, 4 5/8"	100885529	Dodecagon Bolt/Nut/Washer Set, Thru, 5/16-24x1.75, 3 3/8"	100889064
Adapter, 1 1/3" to 4 VCR-F	100881049	Dodecagon Bolt/Nut/Washer Set, Thru, 5/16-24x2.00, 4 1/2"	100889066
Adapter, 1 1/3" to 4 VCR-M	100881050	Dodecagon Bolt/Nut/Washer Set, Thru, 5/16-24x2.25, 4 5/8"	100889068
Adapter, 2 1/8" to 4 VCR-M	100882031	Dodecagon Bolt/Nut/Washer Set, Thru, 1/4-28x1.38, 2 1/8", 2 3/4"	100889151
Adapter, 2 1/8" to 4 VCR-F	100882032	Flange, 1 1/3", Blank, Nonrotatable	100881000
Adapter, 2 1/8" to 8 VCR-F	100882033	Flange, 1 1/3", 0.75", Nonrotatable, Thru	100881004
Adapter, 2 1/8" to 8 VCR-M	100882034	Flange, 1 1/3", Blank, Nonrotatable, Tapped	100881007
Adapter, 2 1/8" to 12 VCR-M	100882035	Flange, 1 1/3", 0.75", Nonrotatable, Tapped	100881011
Adapter, 2 1/8" to 12 VCR-F	100882036	Flange, 1 1/3", Blank, Rotatable, Thru	100881014
Adapter, 2 3/4" to 4 VCR-F	100883054	Flange, 1 1/3", 0.75", Rotatable, Thru	100881018
Adapter, 2 3/4" to 4 VCR-M	100883055	Flange, 1 1/3", Blank, Rotatable, Tapped	100881021
Adapter, 2 3/4" to 8 VCR-M	100883056	Flange, 1 1/3", 0.75", Rotatable, Tapped	100881025
Adapter, 2 3/4" to 8 VCR-F	100883057	Flange, 2 1/8", Blank, Nonrotatable, Thru	100882000
Adapter, 2 3/4" to 12 VCR-F	100883058	Flange, 2 1/8", 0.25", Nonrotatable, Thru	100882001
Adapter, 2 3/4" to 12 VCR-M	100883059	Flange, 2 1/8", 0.50", Nonrotatable, Thru	100882002
Adapter, 3 3/8" to 4 VCR-M	100884032	Flange, 2 1/8", 0.75", Nonrotatable, Thru	100882003
Adapter, 3 3/8" to 4 VCR-F	100884033	Flange, 2 1/8", 1.00", Nonrotatable, Thru	100882004
Adapter, 3 3/8" to 8 VCR-M	100884034	Flange, 2 1/8", Blank, Nonrotatable, Tapped	100882005
Adapter, 3 3/8" to 8 VCR-F	100884035	Flange, 2 1/8", 0.25", Nonrotatable, Tapped	100882006
Adapter, 3 3/8" to 12 VCR-M	100884036	Flange, 2 1/8", 0.50", Nonrotatable, Tapped	100882007
Adapter, 3 3/8" to 12 VCR-F	100884037	Flange, 2 1/8", 0.75", Nonrotatable, Tapped	100882008
Adapter, ISO-KF to CF, NW 16 to 1-1/3" CF	100315601	Flange, 2 1/8", 1.00", Nonrotatable, Tapped	100882009
Adapter, ISO-KF to CF, NW 25 to 2-3/4" CF	100315603	Flange, 2 1/8", Blank, Rotatable, Thru	100882010
Adapter, ISO-KF to CF, NW 40 to 2-3/4" CF	100315605	Flange, 2 1/8", 0.25", Rotatable, Thru	100882012
Adapter, ISO-KF to CF, NW 50 to 4-1/2" CF	100315606	Flange, 2 1/8", 0.50", Rotatable, Thru	100882013
Adapter, ISO-KF to CF, NW 16 to 2-3/4" CF	100315611	Flange, 2 1/8", 0.75", Rotatable, Thru	100882014
Adapter, ISO-KF to CF, NW 25 to 2 1/8" CF	100319812	Flange, 2 1/8", Blank, Rotatable, Tapped	100882015
Adapter, ISO-KF to CF, NW 50 to 2 3/4" CF	100319813	Flange, 2 1/8", 0.25", Rotatable, Tapped	100882016
Adapter, MF to CF, NW 63 to 4.5" CF	100762206	Flange, 2 1/8", 0.50", Rotatable, Thru	100882017
Bellows Section, 1 1/3"	100881045	Flange, 2 1/8", 0.75", Rotatable, Thru	100882018
Bellows Section, 2 1/8"	100882028	Flange, 2 1/8", 1.00", Rotatable, Tapped	100882019
Bellows Section, 2 3/4"	100883047	Flange, 2 1/8", Blank, Rotatable, Thru	100883000
Bellows Section, 3 3/8"	100884025	Flange, 2 3/4", 0.25", Nonrotatable, Thru	100883001
Bolt/Nut Set, Double-Sided, 8-32x1.25, 1 1/3"	100889123	Flange, 2 3/4", 0.50", Nonrotatable, Thru	100883002
Bolt/Nut Set, Double-Sided, 8-32x1.25, 1 1/3"	100889124	Flange, 2 3/4", 0.75", Nonrotatable, Thru	100883003
Bolt/Nut Set, Double-Sided, 1/4-28x1.75, 2 1/8", 2 3/4"	100889125	Flange, 2 3/4", 1.00", Nonrotatable, Thru	100883004
Bolt/Nut Set, Double-Sided, 1/4-28x2.00, 2 3/4"	100889126	Flange, 2 3/4", Blank, Nonrotatable, Tapped	100883005
Bolt/Nut Set, Double-Sided, 5/16-24x2.75, 4 1/2"	100889127	Flange, 2 3/4", 0.25", Nonrotatable, Tapped	100883006
Bolt/Nut Set, Double-Sided, 5/16-24x3.00, 4 5/8"	100889128	Flange, 2 3/4", 0.50", Nonrotatable, Tapped	100883007
Bolt/Nut Set, Double-Sided, 5/16-24x2.50, 3 3/8"	100889130	Flange, 2 3/4", 0.75", Nonrotatable, Tapped	100883008
Bolt/Nut Set, Double-Sided, 1/4-28x2.50, 2 3/4"	100889153	Flange, 2 3/4", Blank, Rotatable, Thru	100883009
Bolt/Nut Set, Thru, 8-32x0.75, 1 1/3"	100889047	Flange, 2 3/4", 0.25", Rotatable, Thru	100883010
Bolt/Nut Set, Thru, 8-32x0.75, 1 1/3"	100889048	Flange, 2 3/4", 0.50", Rotatable, Thru	100883011
Bolt/Nut Set, Thru, 1/4-28x1.25, 2 1/8", 2 3/4"	100889049	Flange, 2 3/4", 0.75", Rotatable, Thru	100883012
Bolt/Nut Set, Thru, 5/16-24x1.75, 3 3/8"	100889051	Flange, 2 3/4", Blank, Rotatable, Tapped	100883013
Bolt/Nut Set, Thru, 5/16-24x2.00, 4 1/2"	100889053	Flange, 2 3/4", 0.25", Rotatable, Tapped	100883014
Bolt/Nut Set, Thru, 5/16-24x2.25, 4 5/8"	100889055	Flange, 2 3/4", 0.50", Rotatable, Tapped	100883015
Bolt/Nut Set, Thru, 8-32x0.87, 1 1/3"	100889147	Flange, 2 3/4", 0.75", Rotatable, Tapped	100883016
Bolt/Nut Set, Thru, 8-32x0.87, 1 1/3"	100889148	Flange, 2 3/4", 1.00", Rotatable, Tapped	100883017
Bolt/Nut Set, Thru, 1/4-28x1.38, 2 1/8", 2 3/4"	100889150	Flange, 2 3/4", Blank, Nonrotatable, Tapped	100883018
Bolt Set, Tapped, 8-32x0.56, 1 1/3"	100889029	Flange, 2 3/4", 0.25", Nonrotatable, Tapped	100883019
Bolt Set, Tapped, 8-32x0.62, 1 1/3"	100889030	Flange, 2 3/4", 0.50", Nonrotatable, Tapped	100883020
Bolt Set, Tapped, 8-32x0.75, 1 1/3"	100889031	Flange, 2 3/4", 0.75", Nonrotatable, Tapped	100883021
Bolt Set, Tapped, 8-32x0.50, 1 1/3"	100889032	Flange, 2 3/4", 1.00", Nonrotatable, Tapped	100883022
Bolt Set, Tapped, 1/4-28x1.00, 2 1/8", 2 3/4"	100889033	Flange, 2 3/4", 1.25", Nonrotatable, Tapped	100883023
Bolt Set, Tapped, 5/16-24x1.25, 3 3/8", 4 1/2", 4 5/8"	100889035	Flange, 2 3/4", 1.50", Nonrotatable, Tapped	100883024
Copper Gasket, Etched, 1 1/3"	100889103	Flange, 2 3/4", Blank, Nonrotatable, Tapped	100883025
Copper Gasket, Etched, 2 1/8"	100889104	Flange, 2 3/4", 0.25", Nonrotatable, Tapped	100883026
Copper Gasket, Etched, 2 3/4"	100889105	Flange, 2 3/4", 0.50", Nonrotatable, Tapped	100883027
Copper Gasket, Etched, 3 3/8"	100889106	Flange, 2 3/4", 0.75", Nonrotatable, Tapped	100883028
Copper Gasket, Etched, 4 1/2"	100889107	Flange, 2 3/4", 1.00", Nonrotatable, Tapped	100883029
Copper Gasket, Etched, 4 5/8"	100889108	Flange, 2 3/4", 1.25", Nonrotatable, Tapped	100883030

Type	Part Number	Type	Part Number
Flange, 2 3/4", 0.50", Nonrotatable, Thru	100883002	Full Nipple, 1 1/3", 0.75"	100881047
Flange, 2 3/4", 0.75", Nonrotatable, Thru	100883003	Full Nipple, 2 1/8", 1.00"	100882041
Flange, 2 3/4", 1.00", Nonrotatable, Thru	100883004	Full Nipple, 2 3/4", 1.50"	100883050
Flange, 2 3/4", 1.25", Nonrotatable, Thru	100883005	Full Nipple w/ Screen, 2 3/4", 1.50"	100883069
Flange, 2 3/4", 1.50", Nonrotatable, Thru	100883006	Full Nipple, 3 3/8", 2.00"	100884028
Flange, 2 3/4", Blank, Nonrotatable, Tapped	100883007	Full Nipple, 4 1/2", 2.50"	100885033
Flange, 2 3/4", 0.25", Nonrotatable, Tapped	100883008	Full Nipple 4 5/8", 3.00"	100885532
Flange, 2 3/4", 0.50", Nonrotatable, Tapped	100883009		
Flange, 2 3/4", 0.75", Nonrotatable, Tapped	100883010	Half Nipple, 1 1/3", .75"	100881046
Flange, 2 3/4", 1.00", Nonrotatable, Tapped	100883011	Half Nipple, 2 1/8", 1.00"	100882040
Flange, 2 3/4", 1.25", Nonrotatable, Tapped	100883012	Half Nipple, 2 3/4", 1.50"	100883049
Flange, 2 3/4", 1.50", Nonrotatable, Tapped	100883013	Half Nipple, 3 3/8", 2.00"	100884027
Flange, 2 3/4", Blank, Rotatable, Thru	100883014	Half Nipple, 4 1/2", 2.50"	100885032
Flange, 2 3/4", 0.25", Rotatable, Thru	100883015	Half Nipple, 4 5/8", 3.00"	100885531
Flange, 2 3/4", 0.50", Rotatable, Thru	100883016		
Flange, 2 3/4", 0.75", Rotatable, Thru	100883017	Plate Nut Set, 8-32, 1 1/3"	100889071
Flange, 2 3/4", 1.00", Rotatable, Thru	100883018	Plate Nut Set, 1/4-28, 2 3/4"	100889072
Flange, 2 3/4", 1.25", Rotatable, Thru	100883019	Plate Nut Set, 5/16-24, 3 3/8"	100889073
Flange, 2 3/4", 1.50", Rotatable, Thru	100883020	Plate Nut Set, 5/16-24, 4 1/2"	100889074
Flange, 2 3/4", Blank, Rotatable, Tapped	100883021	Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 8-32x0.75, 1 1/3"	100889077
Flange, 2 3/4", 0.25", Rotatable, Tapped	100883022	Plate Nut/Bolt Set: 12 Plate Nuts, 24 Bolts/Washers, 1/4-28x1.25, 2 3/4"	100889079
Flange, 2 3/4", 0.50", Rotatable, Tapped	100883023	Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24x1.75, 3 3/8"	100889081
Flange, 2 3/4", 0.75", Rotatable, Tapped	100883024	Plate Nut/Bolt Set: 16 Plate Nuts, 32 Bolts/Washers, 5/16-24x2.00, 4 1/2"	100889083
Flange, 2 3/4", 1.00", Rotatable, Tapped	100883025		
Flange, 2 3/4", 1.25", Rotatable, Tapped	100883026	Silver-Plated Copper Gasket (1), 1 1/3"	100889181
Flange, 2 3/4", 1.50", Rotatable, Tapped	100883027	Silver-Plated Copper Gasket (1), 2 1/8"	100889182
Flange, 2 3/4", 1.75", Nonrotatable, Thru	100883064	Silver-Plated Copper Gasket (1), 2 3/4"	100889183
Flange, 2 3/4", 1.75", Rotatable, Thru	100883065	Silver-Plated Copper Gasket (1), 3 3/8"	100889184
Flange, 2 3/4", 1.75", Nonrotatable, Tapped	100883066	Silver-Plated Copper Gasket (1), 4 1/2"	100889185
Flange, 2 3/4", 1.75", Rotatable, Tapped	100883067	Silver-Plated Copper Gasket (1), 4 5/8"	100889186
Flange, 3 3/8", Blank, Nonrotatable, Thru	100884000	Tee, 1 1/3"	100881028
Flange, 3 3/8", 1.50", Nonrotatable, Thru	100884001	Tee, 2 1/8"	100882042
Flange, 3 3/8", 2.00", Nonrotatable, Thru	100884002	Tee, 2 3/4"	100883028
Flange, 3 3/8", Blank, Nonrotatable, Tapped	100884003	Tee, 3 3/8"	100884012
Flange, 3 3/8", 1.50", Nonrotatable, Tapped	100884004		
Flange, 3 3/8", 2.00", Nonrotatable, Tapped	100884005	Thin Wall Metal Hose, 1.63", 1 1/3"	100881032
Flange, 3 3/8", Blank, Rotatable, Thru	100884006	Thin Wall Metal Hose, 1.63", 1 1/3"	100881033
Flange, 3 3/8", 1.50", Rotatable, Thru	100884007	Thin Wall Metal Hose, 1.63", 1 1/3"	100881034
Flange, 3 3/8", 2.00", Rotatable, Thru	100884008	Thin Wall Metal Hose, 1.38", 2 1/8"	100882020
Flange, 3 3/8", Blank, Rotatable, Tapped	100884009	Thin Wall Metal Hose, 1.38", 2 1/8"	100882021
Flange, 3 3/8", 1.50", Rotatable, Tapped	100884010	Thin Wall Metal Hose, 1.38", 2 1/8"	100882022
Flange, 3 3/8", 2.00", Rotatable, Tapped	100884011	Thin Wall Metal Hose, 2.50", 2 3/4"	100883032
Flange, 4 1/2", Blank, Nonrotatable, Thru	100885000	Thin Wall Metal Hose, 2.50", 2 3/4"	100883033
Flange, 4 1/2", 1.50", Nonrotatable, Thru	100885001	Thin Wall Metal Hose, 2.50", 2 3/4"	100883034
Flange, 4 1/2", 2.00", Nonrotatable, Thru	100885002	Thin Wall Metal Hose, 3.25", 3 3/8"	100884016
Flange, 4 1/2", 2.50", Nonrotatable, Thru	100885003	Thin Wall Metal Hose, 3.25", 3 3/8"	100884017
Flange, 4 1/2", Blank, Nonrotatable, Tapped	100885004	Thin Wall Metal Hose, 3.25", 3 3/8"	100884018
Flange, 4 1/2", 1.50", Nonrotatable, Tapped	100885005	Thin Wall Metal Hose, 6.75", 4 1/2"	100885020
Flange, 4 1/2", 2.00", Nonrotatable, Tapped	100885006	Thin Wall Metal Hose, 6.75", 4 1/2"	100885021
Flange, 4 1/2", 2.50", Nonrotatable, Tapped	100885007	Thin Wall Metal Hose, 6.75", 4 1/2"	100885022
Flange, 4 1/2", Blank, Rotatable, Thru	100885008		
Flange, 4 1/2", 1.50", Rotatable, Thru	100885009	Viton Seal, Beveled Edge (5), 1 1/3"	100889020
Flange, 4 1/2", 2.00", Rotatable, Thru	100885010	Viton Seal, Beveled Edge (5), 2 1/8"	100889021
Flange, 4 1/2", 2.50", Rotatable, Thru	100885011	Viton Seal, Beveled Edge (5), 2 3/4"	100889022
Flange, 4 1/2", Blank, Rotatable, Tapped	100885012	Viton Seal, Beveled Edge (5), 3 3/8"	100889023
Flange, 4 1/2", 1.50", Rotatable, Tapped	100885013	Viton Seal, Beveled Edge (5), 4 1/2"	100889024
Flange, 4 1/2", 2.00", Rotatable, Tapped	100885014	Viton Seal, Beveled Edge (5), 4 5/8"	100889025
Flange, 4 1/2", 2.50", Rotatable, Tapped	100885015		
Flange, 4 5/8", Blank, Nonrotatable, Thru	100885500		
Flange, 4 5/8", 3.00", Nonrotatable, Thru	100885501		
Flange, 4 5/8", Blank, Nonrotatable, Tapped	100885502		
Flange, 4 5/8", 3.00", Nonrotatable, Tapped	100885503		
Flange, 4 5/8", Blank, Rotatable, Thru	100885504		
Flange, 4 5/8", 3.00", Rotatable, Thru	100885505		
Flange, 4 5/8", Blank, Rotatable, Tapped	100885506		
Flange, 4 5/8", 3.00", Rotatable, Tapped	100885507		

